

JVC[®]
PROFESSIONAL

PRELIMINARY

TM-H1375SU

13" High Resolution,
Multi-Purpose Color Video Monitor

New Product News



- High resolution more than 750 TV lines
- NTSC/PAL compatibility
- Underscan function available
- Wired remote functions

- 16:9/4:3 switchable aspect ratio
- On-screen menu for picture adjustment
- Rugged metal cabinet

Features

- A/B two composite video input channels with bridged connection capability
- S-VHS (4-pin) input common to B channel with bridged connection capability
- On-screen menu for precise picture adjustment
- PHASE/CHROMA/BRIGHT/CONTRAST direct access adjustment
- Wired remote control functions for A/B input channel selection and for 4:3/16:9 aspect ratio changeover

Specifications

Model	TM-H1375SU	
Type	Color Video Monitor	
Color System	NTSC/PAL	
Scanning Frequency	H: 15.75kHz (NTSC)/15.625kHz (PAL) V: 50/60Hz	
CRT	13" (diagonally measured) Dot pitch 0.28mm	
Horizontal Resolution	More than 750 TV lines (Y/C input mode)	
Power Requirement	120V AC, 50/60Hz	
Power Consumption	1.2A (tentative)	
Colour Temperature	6500/9300' selectable	
Input Terminals		
Input A	Composite	1 line, BNC connector × 2, 1.0V(p-p), 75 ohms, negative sync, auto-termination, bridged output possible
Input B	Composite	1 line, BNC connector × 2, 1.0V(p-p), 75 ohms, negative sync, auto-termination, bridged output possible
	Y/C Priority	1 line, mini-DIN 4-pin × 2 Y: 1.0V(p-p), 75 ohms, negative sync C: 0.286V(p-p), 75 ohms (NTSC Burst) 0.3V(p-p), 75 ohms (PAL Burst) auto-termination, bridged output possible
Audio Terminals		RCA pin × 4 for input A and B, 0.5V(rms), high-impedance, bridged output possible
Remote INPUT A/B		1 line, RCA pin × 1
Remote ASPECT		1 line, RCA pin × 1
Audio Speaker		3- ³ / ₁₆ " (8cm) round × 1, 1W output (monaural)
Dimensions (W × H × D)		13- ⁵ / ₈ × 12- ¹ / ₄ × 14- ¹³ / ₁₆ inches 346 × 310 × 375mm
Weight		30 lbs. (13.2kg)

JVC® DISTRIBUTED BY

JVC PROFESSIONAL PRODUCTS COMPANY
DIVISION OF JVC AMERICAS CORP.
1700 Valley Road, Wayne, N.J. 07470
TEL: (973) 315-5000, (800) 582-5825
FAX: (973) 315-5030
E-mail: proinfo@jvc.com

JVC CANADA INC.

21 Finchdene Square, Scarborough, Ontario M1X 1A7
TEL: (416) 293-1311 FAX: (416) 293-8208
Internet Web Site <http://www.jvcpro.com/>

Design and specifications subject to change without notice.



Certificate No. EC96J1049



ISO9001/No. FM26586

■ The Hachioji Plant of Victor Company of Japan, Ltd., has received ISO14001 Certification under the global standard for environmental management.