

Color Monitor

TM-H1375SU 13"

NTSC/PAL

90

- High resolution more than 750 TV lines
- NTSC/PAL compatibility
- Underscan function available
- Wired remote functions
- 16:9/4:3 switchable aspect ratio
- On-screen menu for picture adjustment
- Rugged metal cabinet
- Optional RK-A140E rack mount



Type	Color video monitor
Color system	NTSC/PAL
Scanning frequency	H: 15.734 kHz (NTSC) / 15.625 kHz (PAL) , V: 50/59.94 Hz
CRT	13" (diagonally measured), stripe pitch 0.28 mm
Horizontal resolution	More than 750 TV lines (Y/C input mode)
Power requirements	120 V AC, 50/60 Hz
Power consumption	1.1 A
Color temperature	6,500K/9300K selectable
Input terminals	
1) Input A:	
Composite	1 line, BNC connector x 2, 1.0 V (p-p), 75 ohms, negative sync., auto-termination, bridged-output possible
2) Input B:	
Composite	1 line, BNC connector x 2, 1.0 V (p-p), 75 ohms, negative sync., auto-termination, bridged-output possible
Y/C	1 line, mini-DIN 4-pin x 2 Y: 1.0 V (p-p), 75 ohms, negative sync. C: 0.3 V (p-p) (PAL) / 0.286 V (p-p) (NTSC), 75 ohms auto-termination, bridged output possible
Audio terminals	RCA pin x 4 for inputs A and B, 0.5 V (rms), high-impedance bridged-output possible
Remote input A/B	1 line, RCA pin x 1
Remote aspect	1 line, RCA pin x 1
Audio speaker	3-3/16" (8 cm) round x 1, 1 W output (monaural)
Dimensions (WHD)	346 x 310 x 375 mm (13-5/8" x 12-1/4" x 14-13/16")
Weight	13.2 kg (29.1 lbs.)

