GV-PT2U PRO

- Dye sublimation for photo realistic quality
- 50-sheet paper feed
- Print from composite, Y/C, or computer input
- Built-in frame capture
- Field/frame memory
- Windows printer driver
- On Screen menu operation with supplied remote control unit
- JLIP & bidirectional Centronics interfaces

Supplied accessories

- Remote control unit
- Trial pack includes: super-fine coated paper (10 sheets) + ink cartridge
- Printer driver and JLIP video capture software (1.44 MB floppy disk)

Optional Accessories

- Super-fine coated paper pack (PV-50SFSAUP) 50 sheets of paper + ink cartridge
- Super-fine coated label pack (PV-25SFSAUP) 25 sheets of stickers + ink cartridge
- HS-V1 JLIP Player Pack: Featuring new JLIP Movie Player Ver. 1.1 software for editing, as well as computer control of the GV-PT2U PRO and access to a multitude of advanced features.





Print method	Dye sublimation
Output quality	Print pixels: 640 x 480 dots (max.) 16.77 million colors (full color)
Print area (max.)	112 x 84 mm (4-3/8" x 3-1/4")
Paper size	144 x 100 mm (4-1/2" x 3-7/8")
Print speed	Approx. 90 sec./sheet
Paper feed	Automatic (max. 50 sheets)
Control terminals	JLIP & remote pause
PC interface	Bidirectional or Enhanced Parallel Port
Power requirements	AC 120 V, 60 Hz
Power consumption	63 W during printing, 13 W on standby
Dimensions	213 (W) x 90 (H) x 213 (D) mm (8-3/8" x 3-1/2" x 8-3/8")
Weight	Approx. 2.3 kg (4.8 lbs.) with paper tray