


B & W Video Monitors

TM-923U 9"

TM-123U 14"

130



- **9" B&W Video Monitor**
- **High Resolution Pictures**
With 700 lines of horizontal resolution, the monitor provides sharp reproduction of every detail.
- **Looped-through Output**
Convenient looped-through connection is available.
- **Flexible Mounting**
Two TM-923Us can be mounted together in a standard EIA 19" rack using the optional UC-P1016U Rack Mount Adapter.

- **14" B&W Video Monitor**
- **High Resolution Pictures**
With 700 lines of horizontal resolution, the monitor provides sharp reproduction of every detail.
- **Looped-through Output**
Convenient looped-through connection is available.
- **Flexible Mounting**
The TM-123U can be mounted in a standard EIA 19" rack using the optional UC-P1027U Rack Mount Adapter.

MODEL	TM-923U	TM-123U
Picture tube	9", 90° deflection	14", 90° deflection
Horizontal resolution	More than 700 lines (at center)	←
Scanning frequencies	Horizontal: 15.75 kHz Vertical: 60 Hz	←
Input	Video x 1: VS, 1 V(p-p), 75 ohms (BNC)	←
Output (looped-through)	Video x 1: VS, 1 V(p-p), 75 ohms (BNC)	←
S/N ratio	More than 55 dB	←
Video frequency response	15 kHz to 9 MHz	←
Sweep lineanty	Less than 7%	←
Power requirements	120 V AC	←
Power consumption	Approx. 25 W	Approx. 27 W
Ambient temperature range	-10°C to +50°C (14°F to 122°F)	←
Weight	Approx. 6.2 kg (13.7 lbs.)	Approx. 10.5 kg (23.1 lbs.)
Dimensions	8-11/16" (W) x 9-13/16" (H) x 11-1/16" (D)	12-1/2" (W) x 12-3/16" (H) x 12-1/4" (D)