

# D-ILA Video/Data/Graphics Projectors

98

Model	DLA-G10U	DLA-G11U	DLA-G15U	DLA-M15U	DLA-S10U	DLA-C15U
Key Features	True SXGA 2-3:1 zoom lens	True SXGA 2-3:1 zoom lens 350:1 contrast	True SXGA 2-3:1 zoom lens 1500 lumens	True SXGA 1.5:1 fixed lens with shift 1500 lumens	True SXGA 1:1 fixed lens	True SXGA 1:1 fixed lens 1500 lumens
Key Application	Workstation user Presentation Education Entertainment	←	←	Rear projection CRT projector replacement Twin stacking Workstation user Presentation Education Entertainment	Rear projection "Retrobox" engine Workstation user Presentation Education Entertainment	←
Image Device	Three 0.9" D-ILA 1.4 million pixel panels 16.7 million colors (256 levels R,G,B)	←	←	←	←	←
Full Resolution	True SXGA 1,280 x 1,024 (5:4) 1365 x 1024 (4:3)	←	←	←	←	←
Video Resolution	1000 TV lines	←	←	←	←	←
H. Scan Frequency	15 - 82 kHz	←	←	←	←	←
V. Scan Frequency	50 - 78 kHz	←	←	←	←	←
Image Input Signals	RGB HV (BNC, D-sub 15-pin), NTSC, PAL, Composite, Component (BNC), Y/C 4-pin	←	←	←	←	←
Image Output	D-sub 15-pin Computer	←	←	←	←	←
Audio Input	Stereo RCA x 2, Minijack x 1	←	←	←	←	←
Audio Output	Minijack x 1	←	←	←	←	←
Speaker	1 W + 1 W stereo	←	←	←	←	←
Remote Control	Infrared remote, Wired (Minijack), RS-232C (9-pin)	←	←	←	←	←
ANSI Brightness	1000 lumens	1000 lumens	1500 lumens	1500 lumens	1000 lumens	1500 lumens
Contrast Ratio	>250:1	>350:1	>350:1	>350:1	>250:1	>350:1
Projection Lens	2-3:1 (throw distance: screen width) powered zoom	←	←	1.5:1 (throw distance: screen width) with small powered zoom adjustment	1:1 (throw distance: screen width) fixed lens	←
	50% fixed off-set power focus	←	←	30-55% manual shift power focus	without offset power focus	←
Lamp	400 W xenon	420 W xenon short gap	←	←	400 W xenon	420 W xenon short gap
Power Consumption	630 W	←	660 W	←	630 W	660 W
Input Power	100 - 120 V AC, 200 - 240 V AC	←	←	←	←	←
Dimensions (excluding lens)	43 (W) x 25 (H) x 34 (D) cm (16-15/16" x 9-7/8" x 13-7/16")	←	←	←	←	←
Weight	14.8 kg (32.6 lbs.)	←	←	15.4 kg (33.6 lbs.)	14.9 kg (32.9 lbs.)	16 kg (35.0 lbs.)
Provided Accessories	AC cable, wireless remote control, PC connection cable (D-sub 15-pin male to D-sub 15-pin male), adapter for Macintosh, AV cable, BNC-RCA adapter, audio cable, lens cap, operation manual, battery for remote control unit x 2.					

All model numbers, specifications and prices are subject to change without notice.