

Color Monitors

TM-1600SU 16"

TM-2000SU 20"

82



TM-1600SU:

- High 550 Horizontal TV lines resolution picture from unique 16" inch CRT
- Vertical Stripe phosphors
- 16:9 or 4:3 selectable aspect ratio
- Brightness peak suppression system extends tube life
- NTSC / PAL auto selection
- Built in speaker
- User-friendly on-screen graphical menu
- Memory function
- Control lock
- Wired remote control
- Rugged metal cabinet

TM-2000SU:

- 450 Horizontal TV lines resolution picture from 20" inch CRT
- Vertical Stripe phosphors
- 16:9 or 4:3 selectable aspect ratio
- Brightness peak suppression system extends tube life
- NTSC / PAL auto selection
- Built in speaker
- User-friendly on-screen graphical menu
- Memory function
- Control lock
- Wired remote control
- Rugged metal cabinet

Type	Color video monitor
Color system	NTSC/PAL , Auto select
Horizontal resolution	550 TV lines
Power requirements	120 V AC, 50/60 Hz
Video Input A: Composite	1.0 V (p-p), 75 ohms, negative sync, auto-termination, BNC x 2, bridged out possible
Video Input B: Composite	1.0 V (p-p), 75 ohms, negative sync, auto-termination, BNC x 2, bridged out possible
Video Input B: Y/C	Y: 1.0 V (p-p), 75 ohms, negative sync C: 0.286 V (p-p), 75 ohms (NTSC) C: 0.3 V (p-p), 75 ohms (PAL) Auto termination, DIN 4-pin x 2, bridged out possible
Audio input	RCA pin x 4 for input A and input B channels, bridged out possible
Audio output	1 W
Remote terminal	RCA pin x2, bridged out possible
Dimensions	360 (W) x 334.3 (H) x 393.3 (D) mm (14-1/4" x 13-1/4" x 15-1/2")
Weight	17.2 kg (38 lbs.)

Type	Color video monitor
Power requirements	120 V AC, 50/60 Hz
Color temperature	6,500 degrees K / 9,300 degrees K (selectable)
Video Input B: Composite	1.0 V (p-p), 75 ohms, negative sync, auto-termination, BNC x 2, bridged out possible
Video Input B: Y/C	Y: 1.0 V (p-p), 75 ohms, negative sync C: 0.286 V (p-p), 75 ohms (NTSC) C: 0.3 V (p-p), 75 ohms (PAL) Auto termination, DIN 4-pin x 2, bridged out possible
Audio input	RCA pin x 4 for input A and input B channels, bridged out possible
Audio output	1 W
Remote terminal	RCA pin x2, bridged out possible
Dimensions	476 (W) x 407.5 (H) x 492 (D) mm (18-3/4" x 16-1/16" x 19-3/8")
Weight	28.5 kg (63 lbs.)