

Full-Square Color Monitor/Receivers

TM-2099U 20"

TM-2799SU 27"

86



- 20" diagonal full square dark tinted CRT
- Super command remote control and scrolling multi-lingual menu — English, French, or Spanish
- Apaceon — a circuit that improves picture clarity by sharpening the transitions between bright and dark to make every detail crisp and sharp
- Front firing speakers with MTS stereo with dbx and SAP for great sound
- Closed caption decoder with text mode delivers flexibility for applications including CATV, teletext, education, and exhibitions
- Two AV input terminals, S-Video and RF inputs, as well as variable audio output (BNC-RCA adapter provided)
- 180-channel frequency synthesizer tuner for direct cable reception of mid, sub-mid, super, hyper, and ultra bands, plus auto channel programming function
- Multi-function timer with sleep mode
- Three-prong power cord

- 27" diagonal full square dark tinted CRT
- Hyper surround sound and front firing speakers create a three-dimensional sound field
- Super command remote control and scrolling multi-lingual menu — English, French, or Spanish
- Closed caption decoder with text mode opens up a host of possibilities for CATV, teletext, education, and exhibitions
- Two AV input terminals, S-Video and RF inputs, as well as variable audio output (BNC-RCA adapter provided)
- 180-channel frequency synthesizer tuner for direct cable reception of mid, sub-mid, super, hyper, and ultra bands, plus auto channel programming function
- Multi-function timer with sleep mode
- Three-prong power cord

Type	Color video monitor/receiver
Color system	NTSC
CRT	20" (diagonally measured), Full Square (FS) CRT
Scanning frequency	H: 15.75 kHz V: 60 Hz
Horizontal resolution	More than 250 TV lines
Power requirements	120 V AC, 60 Hz
Power consumption	1.4 A
Closed caption	Provided with text
Video inputs	
Composite video	1.0 V (p-p), 75 ohms, negative sync., auto-termination, BNC x 1, bridged-out possible
Audio connectors	RCA pin x 4 (stereo in and out)
Audio speaker	Two 5 x 9 cm (2" x 3-9/16"), 1 W + 1 W output
Dimensions	503 (W) x 452 (H) x 493 (D) mm (19-7/8" x 17-7/8" x 19-1/2")
Weight	19.9 kg (43.8 lbs.)
Power cord	Three-prong
Accessories	RM-C340 Remote control unit, BNC connector box

Type	Color video monitor/receiver
Color system	NTSC
CRT	27" (diagonally measured), Full Square (FS) CRT
Scanning frequency	H: 15.75 kHz (NTSC) V: 60 Hz
Horizontal resolution	More than 250 TV lines
Power requirements	120 V AC, 60 Hz
Power consumption	1.8 A
Closed caption	Provided with text
Video inputs	
*Y/C given priority Composite video	1.0 V (p-p), 75 ohms, negative sync., auto-termination, BNC x 1, bridged-out possible
Y/C	Y: 1.0 V (p-p), 75 ohms, negative sync. C: 0.286 V (p-p), 75 ohms
Audio connectors	RCA pin x 4 (stereo in and out) channels, bridged-out possible
Audio speaker	Two 5 x 9 cm (2" x 3-9/16"), 1.2 W + 1.2 W output
Dimensions	654 (W) x 593 (H) x 494 (D) mm (25-3/4" x 23-3/8" x 19-1/2")
Weight	31.1 kg (68.5 lbs.)
Power cord	Three-prong
Accessories	RM-C345 Remote control unit, BNC connector box