

Field/Studio Color Video Monitors

TM-910SU 9"

TM-910SU

- Compact design
- NTSC/PAL Compatible
- Universal Power 100V • 230V AC, 50/60 Hz, and 12V DC via XLR-4 connector
- 16:9/4:3 Changeover switch
- Rugged metal cabinet
- Tally Lamp
- Professional functions, Pulse cross, Underscan, Blue check, Color off, External sync

Screen size	9" diagonally measured
CRT pitch	0.5 mm, stripe
Color system	NTSC/PAL
Power requirements	AC:100-240 V AC, 50/60 Hz, auto detection (UL/CSA approvals at 100-120 V AC, 50/60 Hz) DC:12 V DC
Power consumption	0.57 A (AC 120 V), 3.3 A (DC 12 V)
Power cable	Detachable
H. resolution	300 TV lines
Video input	Composite 2 CH w/loop through Y/C 4 pin w/loop through
Audio input	RCA 2CH w/loop through
External sync	BNC 1CH w/loop through independent terminals
Comb filter(NTSC)	Provided
Underscan	Provided
Pulse cross	Provided
Blue check	Provided
Aspect ratio	4:3/16:9
DC power supply	12 V, XLR 4 pin
Dimensions	220 (W) x 326 (H) x 317 (D)mm (8-11/16" x 12-7/8" x 12-1/2")
Tally lamp	Provided

