

# Triaxial Remote Camera Control System

## RM-P270E

38



RM-270E  
(KY-D29E/27CE/19E)



RM-P270E REAR



Triaxial Adapter (Included with RM-P270E)

- Composite and Y/C outputs
- 4-line intercom system (selectable)
- Programme audio output monitoring
- Extendable to 1,500m (5,000 ft.)
- Serial data link camera control
- Automatic camera phase control for genlock circuit
- 19" rack mountable (2U)
- Optional RM-LP35U and RM-LP80E remote operator control panels

Output signals		
Composite video signal	Y:	1Vp-p 75 ohms x 2
Y/C signal	Y:	1Vp-p (including SYNC) 75 ohms
	C:	0.3Vp-p (burst level) 75 ohmsx2
Intercom	4-wire system: 0 dB, 600 ohms balanced	
	RTS system : -10 dB, 200 ohms, unbalanced	
Audio signal	-20 dBm, 600 ohms	
Input signals		
External sync signal	Composite video signal: 1Vp-p, 75 ohms (bridge connectable) or black burst: 0.45 Vp-p	
RET signal	Composite video signal or VS: 1Vp-p, 75 ohms x 2 (bridge connectable)	
Intercom	4-wire system: 0 dB, 600 ohms	
	RTS system : -10 dB, 200 ohms, unbalanced	
Programme audio	-4 dB, 600 ohms, unbalanced	
Tally	Contact supply or power supply (5-24V DC or 6V AC)	
Others		
Input voltage	220 V/240 V AC, 50/60 Hz	
Power consumption	68 W (including camera with VF-P550)	
Weight	Base station: 10.2 kg (22.5 lbs.)	
	Camera adapter: 2.5 kg (5.5lbs.)	
Ambient temperature	-0°C to 40°C (32°F to 113°F)	

### Optional Remote Control Panels



RM-LP35U



RM-LP80E